



JAX INC.

Approval Date 9/9/2009

Supersedes Date 9/8/2009

Material Safety Data Sheet

Section I. Chemical Product and Company Identification

| | | | |
|-----------------------------|---|--|--|
| Product Name/ Trade Name | JAX MAGNA-PLATE 22 | Product ID No. | 00222 |
| Supplier | JAX INC. W134 N5373 CAMPBELL DRIVE MENOMONEE FALLS, WI 53051 USA | Emergency Contact For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident, Call CHEMTREC: NORTH AMERICA 800-424-9300 INTERNATIONAL +01-703-527-3887 Collect | |
| Synonym(s) | None | | |
| Chemical Name | Lubricating grease | | |
| Chemical Family | Synthetic hydrocarbon | Non-Emergency Contact | JAX: 262-781-8850 JAX/FAX: 262-781-3906 |
| Chemical Formula | Mixture | | |
| Material Uses | Lubricant | | |

Section II. Composition and Information on Ingredients

| Name | PEL/TLV, Source | CAS # | % by Weight |
|--|-----------------------------------|-----------|-------------|
| PROPRIETARY FORMULA. | | | |
| Zinc oxide | 5 mg/m ³ (fumes), OSHA | 1314-13-2 | 5-10 |
| LC₅₀, LD₅₀ of Ingredients | Not available | | |

Section III. Hazards Identification

| | |
|----------------------------------|--|
| Emergency Overview | Potential health risks vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized. |
| Potential Health Effects: | |
| Eye Contact | May cause slight irritation and redness. |
| Skin Contact | Prolonged or repeated skin contact may cause mild irritation. |
| Ingestion | While this product has a low degree of toxicity, ingestion of excessive quantities may cause irritation of the digestive tract. Aspiration into lunge can cause pneumonitis, which can be fatal. |
| Inhalation | Vapor pressure is low. Vapor inhalation under ambient temperature conditions is not normally a problem. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended oil mist exposure limit. |

Continued on Next Page

Section III. Hazards Identification (cont'd)

| | | | | | | |
|------------------|------------------|----------------|---------------------------|------------------------|--|-------------------------------------|
| HMIS Code | Health: 1 | Fire: 1 | Physical Hazard: 0 | HAZARD RATINGS: | 0 Minimal Hazard 1 Slight Hazard 2 Moderate Hazard | 3 Serious Hazard 4 Severe Hazard |
|------------------|------------------|----------------|---------------------------|------------------------|--|-------------------------------------|

Section IV. First Aid Measures

| | |
|---------------------|--|
| Eye Contact | Remove contact lenses, if wearing, and flush eyes with water for 15 minutes. If irritation persists, consult a physician. |
| Skin Contact | Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician. |
| Ingestion | If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician. |
| Inhalation | If exposed to excessive levels of material in the air, move the exposed person to fresh air. Seek medical attention if coughing or respiratory discomfort occurs. |

Section V. Fire and Explosion Data

| | | | |
|---|---|--|---------------|
| Autoignition Temperature | Not available | Sensitivity to Impact | Not available |
| Flash Point | >350°F (177°C), ASTM D 92 | Sensitivity to Static Discharge | Not available |
| Flammable Limits (Approx.) | LOWER Flammable Limit: Not available | UPPER Flammable Limit: | Not available |
| Explosion Hazards | See Lower and Upper Flammable Limits | | |
| Products of Combustion | Oxides of carbon, oxides of nitrogen, smoke and irritating vapors as products of incomplete combustion. | | |
| Firefighting Media and Instructions | Suitable extinguishing media: Carbon dioxide; dry powder; foam; water fog. Unsuitable extinguishing media: Water spray Protective equipment for firefighters: Body-covering protective clothing; full "turn-out" gear; self-contained breathing apparatus | | |
| Special Remarks - Fire and Explosion Hazards | Do not discharge extinguishing waters into streams, rivers and lakes. Water spray may be used to cool containers that are exposed to heat. | | |

Section VI. Accidental Release Measures

| | |
|-----------------------------|---|
| Release or Spill | Recover free product using non-sparking tools and equipment. Add sand, earth, or other suitable absorbent material to the spill area. Minimize breathing vapors. Minimize skin contact. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if the product has entered or may enter sewers, watercourse, or extensive land areas. |
| Environmental Impact | Report spills as required to the appropriate authorities. U.S Coast Guard Regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to the Coast Guard toll-free number 800-424-8802. |

Section VII. Handling and Storage

| | |
|-----------------|--|
| Handling | Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. "Empty" containers retain product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition as they may explode and can cause injury or death. Empty container should be promptly returned to a drum reconditioner. Electrically bond and ground all containers and equipment. |
|-----------------|--|

Continued on Next Page

Section VII. Handling and Storage (cont'd)

Storage Do not use in high-pressure systems in the vicinity of flames, sparks, and hot surfaces. Keep container closed. Store in a cool, dry place. Do not store near heat, sparks, open flame, pilot lights, static electricity, or where temperature may exceed 120°F (49°C). Keep out of reach of children.

Section VIII. Exposure Controls and Personal Protection

Respiratory Protection Use respiratory protection if needed to keep airborne levels below recommended oil mist exposure limits.

Ventilation Use in a well-ventilated area. See Engineering Controls.

Protective Gloves Wear lined non-permeable rubber gloves.

Eye Protection Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Personal Hygiene Wash skin thoroughly after contact, before breaks and meals and at the end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Engineering Controls If user operations generate an oil mist, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended oil mist exposure limits.

Exposure Limit 5 mg/m³ (oil mist) OSHA, for total product; see Section II for component exposure limit(s).

Section IX. Physical and Chemical Properties

| | | | |
|-------------------------------|---|--|-------------------|
| Appearance/Odor | Cream-colored semi-solid with mild petroleum odor | Vapor Pressure | 0.00 mm Hg @ 20°C |
| | | Vapor Density | Not available |
| Odor Threshold | Not available | Percent Volatile | Not available |
| Specific Gravity | Not available | Evaporation Rate | Not available |
| Density | 0.95 - 1.05 @ 25°C | Viscosity | Not available |
| Molecular Weight | Not available | Solubility in Water | Negligible |
| pH | Not available | Coefficient of Water/Oil Distribution | Not available |
| Boiling Point | Not available | Physical State | Semi-solid |
| Freezing/Melting Point | Not available | | |

Section X. Stability and Reactivity Data

Stability Stable under normal temperatures and pressures. **Conditions of Reactivity** Not available

Conditions of Instability Not available

Conditions and Materials to Avoid Avoid heat, open flames, strong acids, strong bases, and oxidizing agents.

Hazardous Polymerization Hazardous polymerization will not occur.

Hazardous Decomposition Products Oxides of carbon, oxides of nitrogen, smoke and irritating vapors as products of incomplete combustion.

Section XI. Toxicological Information

| | | | |
|---------------------------------------|---|---------------------------------------|---------------|
| Routes of Entry | Dermal contact, eye contact, inhalation, ingestion. | Ingestion | Not available |
| Toxicity to Animals | Not available | Inhalation | Not available |
| Effects of Acute Exposure | Not available | Toxically Synergistic Products | Not available |
| Acute Effects of Sensitization | Not available | | |
| Chronic Effects on Humans: | | | |
| Carcinogenic Effects | This product does not contain a carcinogen or potential carcinogen as listed by NTP, IARC, or OSHA [29 CFR 1910.1200(D)#4]. | | |
| Mutagenic Effects | No data available to indicate any components present at greater than 0.1% may present a mutagenic hazard. | | |

Continued on Next Page

Section XI. Toxicological Information (cont'd)

| | |
|-----------------------------|--|
| Teratogenic Effects | No data available to indicate any components present at greater than 0.1% may present a teratogenic hazard. |
| Reproductive Effects | No data available to indicate any components present at greater than 0.1% may present a reproductive hazard. |

Section XII. Ecological Information

| | |
|--------------------|--|
| Ecotoxicity | There is no data available on the adverse effects of this material on the environment. |
|--------------------|--|

Section XIII. Disposal Considerations

| | |
|-----------------------|--|
| Waste Disposal | Consult federal, state or local authorities for proper disposal and reporting procedures. All disposals must comply with federal, state and local regulations. |
|-----------------------|--|

Section XIV. Transportation Information

| | |
|-----------------------|---------------|
| U.S. D.O.T. | |
| Shipping Name: | Not regulated |
| UN Number: | None |
| Hazard Class: | None |
| Packing Group: | None |
| Remarks | None |

Section XV. Regulatory Information

| | |
|--------------------------------------|--|
| U.S. Federal Regulations: | |
| CERCLA | Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is regulated by 40 CFR 302.4 : None |
| SARA (Section 313) | This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations: Zinc oxide, CAS #1314-13-2, present at 5-10% |
| SARA Extremely Hazardous List | This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: None |
| TSCA Inventory | All components of this material are on the U.S. TSCA Inventory. |
| California Prop. 65 | This product contains the following chemical(s) known to the State of California to cause birth defects or other reproductive harm: None |

International Regulations:

| | |
|--------------------|---|
| Canada | All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR. |
| Japan MITI | Not available |
| Australia | Not available |
| Switzerland | Not available |

Section XVI. Other Information

| | |
|--|---------------------------------|
| Approval Date | 9/9/2009 |
| Supersedes Date | 9/8/2009 |
| Prepared by | Technical Services 262-781-8850 |
| Sections Revised Since Last Version | Section I |

The information and recommendations contained herein are, to the best of JAX INC.'s knowledge and belief, accurate and reliable as of the date issued. JAX INC. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC. shall not be liable for any loss or damage based up on the criteria supplied by the developers of these rating systems, together with JAX INC.'s interpretation of the available data.