



JAX INC.

Approval Date 2/9/2009

Supersedes Date 7/2/2007

Material Safety Data Sheet

Section I. Chemical Product and Company Identification

Product Name/ Trade Name	JAX MAGNA-PLATE PM 220	Product ID No.	44220
Supplier	JAX INC. W134 N5373 CAMPBELL DRIVE MENOMONEE FALLS, WI 53051 USA	Emergency Contact For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident, Call CHEMTREC: NORTH AMERICA 800-424-9300 INTERNATIONAL +01-703-527-3887 Collect	
Synonym(s)	None		
Chemical Name	Petroleum lubricating oil		
Chemical Family	Petroleum hydrocarbon oil blend	Non-Emergency Contact	JAX: 262-781-8850 JAX/FAX: 262-781-3906
Chemical Formula	Mixture		
Material Uses	Lubricant		

Section II. Composition and Information on Ingredients

Name	PEL/TLV, Source	CAS #	% by Weight
PROPRIETARY FORMULA. This material is essentially lubricating oil with corrosion inhibitor and antiwear compounds.	5 mg/m ³ (mist), OSHA	Mixture	100.0
LC₅₀, LD₅₀ of Ingredients	Not available		

Section III. Hazards Identification

Emergency Overview	Potential health risks vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.
Potential Health Effects:	
Eye Contact	Not expected to cause prolonged or significant eye irritation.
Skin Contact	May cause slight irritation.
Ingestion	Not expected to be harmful if swallowed.
Inhalation	May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit.

Continued on Next Page

Section III. Hazards Identification (cont'd)

HMIS Code	Health: 1	Fire: 1	Physical Hazard: 0	HAZARD RATINGS	
				0 Minimal Hazard 1 Slight Hazard 2 Moderate Hazard	3 Serious Hazard 4 Severe Hazard

Section IV. First Aid Measures

Eye Contact	Remove contact lenses, if worn, and flush eyes with water. If irritation persists, consult a physician.
Skin Contact	Remove clothing and shoes if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician.
Ingestion	If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician.
Inhalation	If exposed to excessive levels of material in the air, move the exposed person to fresh air. Seek medical attention if coughing or respiratory discomfort occurs.

Section V. Fire and Explosion Data

Autoignition Temperature	Not available	Sensitivity to Impact	Not available
Flash Point	None available	Sensitivity to Static Discharge	Not available
Flammable Limits (Approx.)	LOWER Flammable Limit: Not available	UPPER Flammable Limit:	Not available
Explosion Hazards	See Lower and Upper Flammable Limits		
Products of Combustion	Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of phosphorus, oxides of zinc, aldehydes, hydrogen sulfide, alkyl mercaptans, smoke and irritating vapors as products of incomplete combustion.		
Firefighting Media and Instructions	Dry chemical, alcohol foam, and carbon dioxide type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on the size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists. The following procedures for this type of product are based on the recommendations in the National Fire Protection Association's Fire Protection Guide on Hazardous Materials. Use water to keep fire-exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for men attempting to stop a leak. Water spray may be used to flush spills away from explosives. Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.		
Special Remarks - Fire and Explosion Hazards	For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Leaks/ruptures in high-pressure systems using materials of this type can create a fire hazard when in the vicinity of ignition sources (open flame, pilot lights, sparks or electric arcs).		

Section VI. Accidental Release Measures

Release or Spill	Recover free product using non-sparking tools and equipment. Add sand, earth, or other suitable absorbent material to the spill area. Minimize breathing vapors. Minimize skin contact. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if the product has entered or may enter sewers, watercourse, or extensive land areas.
Environmental Impact	Report spills as required to the appropriate authorities. U.S Coast Guard Regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to the Coast Guard toll-free number 800-424-8802.

Section VII. Handling and Storage

Handling	Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. "Empty" containers retain product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition as they may explode and can cause injury or death. Empty container should be promptly returned to a drum reconditioner.
-----------------	---

Continued on Next Page

Section VII. Handling and Storage (cont'd)

Storage Do not use in high-pressure systems in the vicinity of flames, sparks and hot surfaces. Keep container closed. Do not store near heat, sparks, open flame, pilot lights, static electricity, or where temperature may exceed 120°F (49°C).

Section VIII. Exposure Controls and Personal Protection

Respiratory Protection Use respiratory protection if needed to keep airborne levels below recommended mineral oil mist exposure limits.

Ventilation Use in a well-ventilated area. See Engineering Controls.

Protective Gloves Any lined non-permeable rubber gloves.

Eye Protection Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Personal Hygiene Wash skin thoroughly after contact, before breaks and meals and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Engineering Controls If user operations generate an oil mist, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended mineral oil mist exposure limits.

Exposure Limit See Section II.

Section IX. Physical and Chemical Properties

Appearance/Odor	Clear to amber colored lube oil with little or no odor	Vapor Pressure	Nil
		Vapor Density	Not available
Odor Threshold	Not available	Percent Volatile	Nil
Specific Gravity	Not available	Evaporation Rate	Nil
Density	Not available	Viscosity	Not available
Molecular Weight	Not available	Solubility in Water	Nil
pH	Not available	Coefficient of Water/Oil Distribution	Not available
Boiling Point	Not available	Physical State	Liquid
Freezing/Melting Point	Not available		

Section X. Stability and Reactivity Data

Stability Stable under normal temperatures and pressures. **Conditions of Reactivity** Not available

Conditions of Instability Not available

Conditions and Materials to Avoid Avoid contact with heat, open flames, and oxidizing agents.

Hazardous Polymerization Hazardous polymerization will not occur.

Hazardous Decomposition Products Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of phosphorus, oxides of zinc, aldehydes, hydrogen sulfide, alkyl mercaptans, smoke and irritating vapors as products of incomplete combustion.

Section XI. Toxicological Information

Routes of Entry Dermal contact, eye contact, inhalation, ingestion. **Ingestion** Not available

Toxicity to Animals Not available **Inhalation** Not available

Effects of Acute Exposure Not available **Toxically Synergistic Products** Not available

Acute Effects of Sensitization Not available

Chronic Effects on Humans:

Carcinogenic Effects This product does not contain a carcinogen or potential carcinogen as listed by NTP, IARC, or OSHA [29 CFR 1910.1200(D)#4].

Mutagenic Effects No data available to indicate any components present at greater than 0.1% may present a mutagenic hazard.

Continued on Next Page

Section XI. Toxicological Information (cont'd)

Teratogenic Effects	No data available to indicate any components present at greater than 0.1% may present a teratogenic hazard.
Reproductive Effects	No data available to indicate any components present at greater than 0.1% may present a reproductive hazard.

Section XII. Ecological Information

Ecotoxicity	There is no data available on the adverse effects of this material on the environment.
--------------------	--

Section XIII. Disposal Considerations

Waste Disposal	Consult federal, state or local authorities for proper disposal and reporting procedures. All disposals must comply with federal, state and local regulations.
-----------------------	--

Section XIV. Transportation Information

U.S. D.O.T.			
Shipping Name:	Not regulated	UN Number:	None
Hazard Class:	None	Packing Group:	Not applicable
Remarks	None		

Section XV. Regulatory Information

U.S. Federal Regulations:	
CERCLA	Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is regulated by 40 CFR 302.4 : None
SARA (Section 313)	This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations: None
SARA Extremely Hazardous List	This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: None
TSCA Inventory	All components of this material are on the U.S. TSCA Inventory.
California Prop. 65	WARNING: This product contains the following chemical(s) known to the State of California to cause birth defects or other reproductive harm: < 0.002% cadmium; < 0.002% lead; < 0.002% arsenic

International Regulations:

Canada	All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR.
Japan MITI	Not available
Australia	Not available
Switzerland	Not available

Section XVI. Other Information

Approval Date	2/9/2009
Supersedes Date	7/2/2007
Prepared by	Technical Services 262-781-8850
Sections Revised Since Last Version	Section I

The information and recommendations contained herein are, to the best of JAX INC.'s knowledge and belief, accurate and reliable as of the date issued. JAX INC. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC. shall not be liable for any loss or damage based up on the criteria supplied by the developers of these rating systems, together with JAX INC.'s interpretation of the available data.